

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number
WO 2005/068749 A1

(51) International Patent Classification⁷: **E04F 21/00**,
F16M 7/00, E06B 1/60

[DK/DK]; Nørreled 13, Hou, DK-8300 Odder (DK).
NIELSEN, Stig [DK/DK]; Broagervej 25, DK-6000
Kolding (DK).

(21) International Application Number:
PCT/DK2005/000017

(74) Agent: **INSPICOS A/S**; Bøge Allé 5, P.O. Box 45,
DK-2970 Hørsholm (DK).

(22) International Filing Date: 13 January 2005 (13.01.2005)

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2004 00029 13 January 2004 (13.01.2004) DK
PA 2004 00840 28 May 2004 (28.05.2004) DK
PA 2004 01700 4 November 2004 (04.11.2004) DK

(71) Applicant (for all designated States except US): **ITOOLS**
APS [DK/DK]; Skovdalsvej 4, 2., DK-8300 Odder (DK).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **BRUHN, Ulrik**

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: A DISTANCE PIECE



(57) Abstract: The invention provides a distance piece e.g. to replace a traditional wedge e.g. for fitting a window to an opening of a building. The distance piece has two parts (2, 3) which are separable by a separation part. During use, the separation part is inserted between the two parts which are forced apart. In this condition, the separation part is locked to leave the distance piece in the expanded condition. After final fixation of the building component, the separation part can be released and moved to a position wherein the two parts are allowed to revert to a collapsed state. In that way, the distance piece facilitates reuse.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report